



TAURUS series

hydraulic blind rivet setting tools



TAURUS 1

Part no. 756 0001

Working range

Blind rivets up to 4 mm Ø alu/steel
(max. mandrel dia. 2,5 mm)

Technical data

Weight: 1,3 kg
Operating air pressure: 5-7 bar
Air hose connection: 6 mm Ø (1/4")
Air consumption: ca. 1,0 ltr. per cycle
Traction power: 4.200 N at 5 bar
Stroke: 15 mm

Nosepieces/accessories

Nosepieces:
17/18 (in working position)
17/24, 17/27 (in tool bottom)
Maintenance wrench SW12/14, SW14/17
1 oil bottle 100 ml
1 oil refill can
Operating instructions with spare parts list



TAURUS 2

Part no. 757 0007

Working range

Blind rivets up to 5 mm Ø all materials and up
to 6 mm Ø alu/steel (max. mandrel dia. 3,2)

Technical data

Weight: 1,6 kg
Operating air pressure: 5-7 bar
Air hose connection: 6 mm Ø (1/4")
Air consumption: ca. 2,3 ltr. per cycle
Traction power: 9.000 N at 5 bar
Stroke: 18 mm

Nosepieces/accessories

Nosepieces:
17/27 (in working position)
17/29, 17/32, 17/36 (in tool bottom)
Maintenance wrench SW12/14, SW14/17
1 oil bottle 100 ml
1 oil refill can
Operating instructions with spare parts list



TAURUS 3

Part no. 758 0002

Working range

Blind rivets up to 6,4 mm Ø all materials
(max. mandrel dia. 4,5 mm)

Technical data

Weight: 1,9 kg
Operating air pressure: 5-7 bar
Air hose connection: 6 mm Ø (1/4")
Air consumption: ca. 4,8 ltr. per cycle
Traction power: 14.000 N at 5 bar
Stroke: 25 mm

Nosepieces/accessories

Nosepieces:
17/36 (in working position)
17/40, 17/45 (in tool bottom)
Maintenance wrench SW12/14, SW14/17
1 oil bottle 100 ml
1 oil refill can
Operating instructions with spare parts list

Authorised UK distributors for:

TAURUS 4



Part no. 759 0001

Working range

Blind rivets up to 6,4 mm Ø all materials and up to 8 mm Ø alu (max. mandrel dia. 4,5 mm)

Technical data

Weight:	2,0 kg
Operating air pressure:	5-7 bar
Air hose connection:	6 mm Ø (1/4")
Air consumption:	ca. 4,8 ltr. per cycle
Traction power:	20.000 N at 5 bar
Stroke:	19 mm

Nosepieces/accessories

Nosepieces:
 17/36 (in working position)
 17/40, 17/45 (in tool bottom)
 Maintenance wrench SW12/14, SW14/17
 1 oil bottle 100 ml
 1 oil refill can
 Operating instructions with spare parts list

TAURUS 5



Basic tool
Part no. 760 0001

Working range

Blind rivets from 6,4 mm Ø all materials, Lockbolts up to 10 mm Ø with corresponding pulling heads

Technical data

Weight:	3,4 kg
Operating air pressure:	5-7 bar
Air hose connection:	6 mm Ø (1/4")
Air consumption:	ca. 6,9 ltr. per cycle
Traction power:	42.000 N at 7 bar
Stroke:	17 mm

Equipment/accessories

1 oil bottle 100 ml
 1 oil refill can
 Operating instructions and spare parts list

TAURUS 6



Basic tool
Part no. 761 0002

Working range

Blind rivets from 6,4 mm Ø all materials, Lockbolts up to 10 mm Ø with corresponding pulling heads

Technical data

Weight:	3,4 kg
Operating air pressure:	5-7 bar
Air hose connection:	6 mm Ø (1/4")
Air consumption:	ca. 6,9 ltr. per cycle
Traction power:	50.000 N at 7 bar
Stroke:	15 mm

Equipment/accessories

1 oil bottle 100 ml
 1 oil refill can
 Operating instructions with spare parts list

Small jaw assembly for TAURUS 1 and 2



for TAURUS 1
Part no. 756 1120

for TAURUS 2
Part no. 757 1077

Operating range

- All alu/steel blind rivets up to Ø 5mm and steel/steel up to Ø 4mm with **TAURUS 1** and **2**
- Very much suitable for recessed riveting locations

Head modules for TAURUS 5 & 6



Head modules for 7,8 mm Titgemeyer TIBULB®*
Part no. 760 0201

Head modules for 9.8 mm Huck Magna-Lok®*
Part no. 760 0202

Further head modules

on request

Versatility as highest priority

The **TAURUS 5** and **6** riveting tools must be adapted to the different kinds of blind rivets and lockbolts through specific pulling head modules.

Authorised UK distributors for:

Avdel southco

BBA

DEJOND

GESIPA

EJOT